

2660

SAFETY HELMET CLASS 1

SIZES: One Size



2668

REPLACEMENT VISOR

SIZES: One Size
Resistance to fogging (N)




HELMET

- ✓ Stroke absorption after conditioning in temperatures of (-30°C) and (0°C)
- ✓ Resistance to penetration after conditioning in temperatures of (-30°C) and (+50°C)
- ✓ Live working symbol (Two Triangles)
- ✓ Working temperature range (-30°C) and (+50°C)
- ✓ Wheel ratchet adjustment
- ✓ Adjustable head circumference from 53-63cm
- ✓ Two level height adjustment feature
- ✓ Electrical insulation (Class 0) 1000V AC, 1500V DC
- ✓ Protection against molten metal splash - symbol MM
- ✓ Protection against lateral deformations - symbol LD

VISOR

- ✓ Level of protection 1.2 (transparent face shield)
- ✓ Level of protection 1.7 (dimmed face shield)
- ✓ Protection against droplets and splashes of liquids (3)
- ✓ Optical powers, light transmission factor, luminance factor of dispersed light Optical Class 1
- ✓ Resistance to medium energy impact (speed stroke up to 120m/s, mass of ball 0.86kg) (B)
- ✓ Protection against short circuit electric arc (8)
- ✓ Protection against thermal hazards of an electric arc, Class 1 (box test; 4kA/0.5s) VLT factor → 75% for class 0
- ✓ Protection against molten metal and hot solids (9)
- ✓ Resistance to surface damage by fine particles (K)

EN STANDARDS



PRODUCT INFORMATION

LIFETIME: 5 Years
SIZES: One Size
COLOUR: White (other colours available)