



0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.
Issue date: 23/10/2024 Revision date: 29/01/2025 Supersedes: 23/10/2024 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 0900 LINEMARKER YELLOW 750ML
Product code : 001802077807
Type of product : Paint
Vaporizer : Aerosol
Product group : End product
Other means of identification : 001802077807FR 0900FR LINEMARKER YELLOW 750ML EUROPE
001802077807PK6 0900 LINEMARKER YELLOW 750ML 6 PACK

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use, Industrial use
Use of the substance/mixture : Spraying paint (spray can)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Tetrosyl Limited
Newgate House
Rochdale – Lancashire OL16 1AT
T 0161 764 5981
ataylor@jamesbriggs.co.uk - www.tetrosyl.com

1.4. Emergency telephone number

Emergency number : +44 (0) 161 620 5400

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.
Harmful to aquatic life with long lasting effects.

0900 LINEMARKER YELLOW 750ML


Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP)



Signal word (GB CLP)

: Danger

Contains

: Acetone; Hydrocarbons, C9, aromatics

Hazard statements (GB CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GB CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing vapours, spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, eye protection.
P264 - Wash hands thoroughly after handling.
P312 - Call a POISON CENTER, doctor if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice, attention.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.
P501 - Dispose of contents/ container in accordance with local regulations.

EUH-statements (GB CLP)

: EUH066 - Repeated exposure may cause skin dryness or cracking.

Child-resistant fastening

: Not applicable

Tactile warning

: Not applicable

2.3. Other hazards

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	Xylene (mixture of isomers) (1330-20-7)(¹), Titanium dioxide (13463-67-7), n-butyl acetate (123-86-4), Acetone (67-64-1), 2-methylpropan-1-ol (78-83-1)(¹), Hydrocarbons, C9, aromatics (64742-95-6), Kaolin (1332-58-7), 2-methoxy-1-methylethyl acetate (108-65-6)(¹), Ethylbenzene (100-41-4)(¹), Methyl methacrylate (80-62-6)(¹), 2-methoxy-1-methylethyl acetate (108-65-6)(¹), Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7), Hydrocarbons, C9, aromatics (128601-23-0), Propan-2-ol (67-63-0)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	Xylene (mixture of isomers) (1330-20-7)(¹), Titanium dioxide (13463-67-7), n-butyl acetate (123-86-4), Acetone (67-64-1), 2-methylpropan-1-ol (78-83-1)(¹), Hydrocarbons, C9, aromatics (64742-95-6), Kaolin (1332-58-7), 2-methoxy-1-methylethyl acetate (108-65-6)(¹), Ethylbenzene (100-41-4)(¹), Methyl methacrylate (80-62-6)(¹), 2-methoxy-1-methylethyl acetate (108-65-6)(¹), Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7), Hydrocarbons, C9, aromatics (128601-23-0), Propan-2-ol (67-63-0)

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)(68476-85-7), Acetone(67-64-1), Hydrocarbons, C9, aromatics(128601-23-0), Kaolin(1332-58-7), n-butyl acetate(123-86-4), Titanium dioxide(13463-67-7), Propan-2-ol(67-63-0), Hydrocarbons, C9, aromatics(64742-95-6), Xylene (mixture of isomers)(1330-20-7)(¹), 2-methoxy-1-methylethyl acetate(108-65-6)(¹), Ethylbenzene(100-41-4)(¹), Methyl methacrylate(80-62-6)(¹), 2-methylpropan-1-ol(78-83-1)(¹), 2-methoxy-1-methylethyl acetate(108-65-6)(¹)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Labelling according to GB CLP (SI 2019:720 as amended)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 UK Index-No.: 649-202-00-6	25 – 50	Flam. Gas 1A, H220 Press. Gas
Acetone	CAS-No.: 67-64-1 EC-No.: 200-662-2 UK Index-No.: 606-001-00-8	20 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C9, aromatics	CAS-No.: 128601-23-0 EC-No.: 918-668-5	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Kaolin	CAS-No.: 1332-58-7 EC-No.: 310-194-1	10 – 20	Not classified
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 UK Index-No.: 607-025-00-1	3.5 – 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
Titanium dioxide	CAS-No.: 13463-67-7 EC-No.: 236-675-5 UK Index-No.: 022-006-002	0.25 – 0.5	Not classified
Propan-2-ol	CAS-No.: 67-63-0 EC-No.: 200-661-7 UK Index-No.: 603-117-00-0	0.25 – 0.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C9, aromatics	CAS-No.: 64742-95-6 EC-No.: 918-668-5 UK Index-No.: 649-356-00-4	0.1 – 0.2	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH066

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Name	Product identifier	%	Labelling according to GB CLP (SI 2019:720 as amended)
Xylene (mixture of isomers)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 UK Index-No.: 601-022-00-9	0.005 – 0.05	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6 EC-No.: 203-603-9 UK Index-No.: 607-195-00-7	0.005 – 0.05	Flam. Liq. 3, H226 STOT SE 3, H336
Ethylbenzene	CAS-No.: 100-41-4 EC-No.: 202-849-4 UK Index-No.: 601-023-00-4	0.005 – 0.05	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Methyl methacrylate	CAS-No.: 80-62-6 EC-No.: 201-297-1 UK Index-No.: 607-035-00-6	0.005 – 0.05	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-methylpropan-1-ol	CAS-No.: 78-83-1 EC-No.: 201-148-0 UK Index-No.: 603-108-00-1	0.005 – 0.05	Flam. Liq. 3, H226 STOT SE 3, H336 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6 EC-No.: 203-603-9 UK Index-No.: 607-195-00-7	0.0000001 – 0.005	Flam. Liq. 3, H226 STOT SE 3, H336

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Xylene (mixture of isomers) (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m ³ o-,m-,p- or mixed isomers 50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers 100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Titanium dioxide (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA)	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m ³

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

n-butyl acetate (123-86-4)	
	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Acetone (67-64-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-methylpropan-1-ol (78-83-1)	
United Kingdom - Occupational Exposure Limits	
Local name	2-Methylpropan-1-ol
WEL TWA (OEL TWA)	154 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	231 mg/m ³
	75 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Kaolin (1332-58-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Kaolin
WEL TWA (OEL TWA)	2 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-methoxy-1-methylethyl acetate (108-65-6)	
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA)	274 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	548 mg/m ³
	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Ethylbenzene (100-41-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethylbenzene

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Ethylbenzene (100-41-4)	
WEL TWA (OEL TWA)	441 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	552 mg/m ³
	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Methyl methacrylate (80-62-6)	
United Kingdom - Occupational Exposure Limits	
Local name	Methyl methacrylate
WEL TWA (OEL TWA)	208 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	416 mg/m ³
	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-methoxy-1-methylethyl acetate (108-65-6)	
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA)	274 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	548 mg/m ³
	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Liquefied petroleum gas
WEL TWA (OEL TWA)	1750 mg/m ³
	1000 ppm
WEL STEL (OEL STEL)	2180 mg/m ³
	1250 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Propan-2-ol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m ³

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Propan-2-ol (67-63-0)	
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
protective clothing	EN ISO 6530

Hand protection:

Protective gloves

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves					EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Yellow.
Odour	: organic solvent.
Odour threshold	: Not available
pH	: Not relevant - substance/mixture is non-soluble (in water).
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: -40 – -2 °C (LPG)
Flash point	: < -40 °C
Lower explosion limit	: 1.4 vol % (LPG)
Upper explosion limit	: 10.9 vol % (LPG)
Vapour pressure	: 590 – 1760 kPa (LPG)
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: 365 °C (LPG)
Decomposition temperature	: Not available
Viscosity, kinematic	: < 20.5 mm ² /s
Explosive properties	: Pressurised container: May burst if heated.

9.2. Other information

VOC content	: 626 g/l
Volatility	: Volatile
Particle characteristics	: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Xylene (mixture of isomers) (1330-20-7)

LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
--------------------	---

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
---------------	---

LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
-----------------------	--

Hydrocarbons, C9, aromatics (64742-95-6)

LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	---

LC50 Inhalation - Rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
-----------------------	--

2-methoxy-1-methylethyl acetate (108-65-6)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
-----------------	--

Methyl methacrylate (80-62-6)

LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	---

2-methoxy-1-methylethyl acetate (108-65-6)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
-----------------	--

Hydrocarbons, C9, aromatics (128601-23-0)

LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	---

LC50 Inhalation - Rat	> 6.193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
-----------------------	---

Propan-2-ol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

Skin corrosion/irritation : Not classified
pH: Not relevant - substance/mixture is non-soluble (in water).

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Serious eye damage/irritation	: Causes serious eye irritation. pH: Not relevant - substance/mixture is non-soluble (in water).
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Propan-2-ol (67-63-0)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Xylene (mixture of isomers) (1330-20-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

n-butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Acetone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

2-methylpropan-1-ol (78-83-1)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

Hydrocarbons, C9, aromatics (64742-95-6)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

2-methoxy-1-methylethyl acetate (108-65-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Methyl methacrylate (80-62-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

2-methoxy-1-methylethyl acetate (108-65-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Hydrocarbons, C9, aromatics (128601-23-0)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

Propan-2-ol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

Xylene (mixture of isomers) (1330-20-7)

LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

2-methylpropan-1-ol (78-83-1)

NOAEL (oral, rat, 90 days)	> 1450 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	--

Hydrocarbons, C9, aromatics (64742-95-6)

NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
Hydrocarbons, C9, aromatics (128601-23-0)	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Aspiration hazard	: Not classified
0900 LINEMARKER YELLOW 750ML	
Vaporizer	Aerosol
Viscosity, kinematic	< 20.5 mm ² /s
Not able to form a pool	Yes
2-methylpropan-1-ol (78-83-1)	
Viscosity, kinematic	38702.757 mm ² /s
Ethylbenzene (100-41-4)	
Viscosity, kinematic	0.6 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)' Remarks on result: 'other:'
Methyl methacrylate (80-62-6)	
Viscosity, kinematic	0.561 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Xylene (mixture of isomers) (1330-20-7)	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

n-butyl acetate (123-86-4)	
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
Acetone (67-64-1)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
2-methylpropan-1-ol (78-83-1)	
LC50 - Fish [1]	1430 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1100 mg/l Test organisms (species): Daphnia pulex
NOEC (chronic)	20 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Hydrocarbons, C9, aromatics (64742-95-6)	
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
Methyl methacrylate (80-62-6)	
LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	69 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 110 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LC50 - Fish [1]	0.362 mg/l
EC50 - Crustacea [1]	0.018 mg/l
ErC50 algae	7.6 mg/l Source: ECOTOX
Hydrocarbons, C9, aromatics (128601-23-0)	
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
12.2. Persistence and degradability	
0900 LINEMARKER YELLOW 750ML	
Persistence and degradability	Not rapidly degradable
Xylene (mixture of isomers) (1330-20-7)	
Persistence and degradability	Not rapidly degradable
Titanium dioxide (13463-67-7)	
Persistence and degradability	Not rapidly degradable
n-butyl acetate (123-86-4)	
Persistence and degradability	Rapidly degradable
Biodegradation	83 %
Acetone (67-64-1)	
Persistence and degradability	Not rapidly degradable
2-methylpropan-1-ol (78-83-1)	
Persistence and degradability	Not rapidly degradable
Hydrocarbons, C9, aromatics (64742-95-6)	
Persistence and degradability	Not rapidly degradable
Kaolin (1332-58-7)	
Persistence and degradability	Not rapidly degradable
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Not rapidly degradable
Ethylbenzene (100-41-4)	
Persistence and degradability	Not rapidly degradable
Methyl methacrylate (80-62-6)	
Persistence and degradability	Not rapidly degradable
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Not rapidly degradable
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Persistence and degradability	Rapidly degradable

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Hydrocarbons, C9, aromatics (128601-23-0)	
Persistence and degradability	Not rapidly degradable
Propan-2-ol (67-63-0)	
Persistence and degradability	Rapidly degradable
Biodegradation	95 %

12.3. Bioaccumulative potential

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
Xylene (mixture of isomers) (1330-20-7)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
Titanium dioxide (13463-67-7)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
Acetone (67-64-1)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
2-methylpropan-1-ol (78-83-1)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
Hydrocarbons, C9, aromatics (64742-95-6)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
Kaolin (1332-58-7)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Component	
Ethylbenzene (100-41-4)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Methyl methacrylate (80-62-6)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Hydrocarbons, C9, aromatics (128601-23-0)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Propan-2-ol (67-63-0)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

0900 LINEMARKER YELLOW 750ML






Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment
---------	--

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: False	Dangerous for the environment: False Marine pollutant: No	Dangerous for the environment: False	Dangerous for the environment: False	Dangerous for the environment: False
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

Contains no substance(s) listed on the UK REACH Candidate List

GB PIC regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains substance(s) listed on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure: Acetone - 67-64-1

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (273/2004)

This product contains substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure (Acetone - 67-64-1)

15.1.2. Other Information

VOC content : 626 g/l

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Abbreviations and acronyms:	
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

0900 LINEMARKER YELLOW 750ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.